

C1_D/R RANGE: Functions, Facilities & Options

FUNCTION / FACILITY / OPTION	MODEL NUMBER							
	C1KD	C1KR	C1LD	C1LR	C1MD	C1MR	C1ND	C1NR
Desk-top sloping top case	U		U		U		U	
Wall-mount sloping front case								
1u rack-mount case		U		U		U		U
Fixed electret microphone on 25cm flexible stem	U	U						
XLR3 microphone socket with selectable phantom power			U	U	U	U	U	U
85-264V AC mains input on IEC connector	U	U	U	U	U	U	U	U
12V DC power input on 2.1mm coaxial battery connector			U		U		U	
TALKBACK output on male XLR3 connector	U	U	U	U	U	U	U	U
REVERSE TALKBACK input on female XLR3 connector	U	U	U	U	U	U	U	U
IFB input on female XLR3 connector					U	U	U	U
Selectable LOOP-THROUGH INTERRUPT mode			U	U				
HEADPHONE output on 6.4mm (¼") jack			U	U	U	U	U	U
HEADSET input/output on female XLR5 connector					U	U	U	U
Separate gain adjustments for headset and stem mic's					U	U	U	U
TALK switch with selectable latch mode & VOX operation			U	U	U	U	U	U
Adjustable TALKBACK output level			U	U	U	U	U	U
TALKBACK output peak level indicator (0dBu & +8dBu)							U	U
Selectable monitoring of IFB or REV TB inputs							U	U
Signal presence (CALL) LED on selected input			U	U	U	U	U	U
LS LEVEL control	U	U	U	U	U	U	U	U
LS CUT switch			U	U	U	U	U	U
LS DIM: fixed, 20dB	U	U						
LS DIM: adjustable, 0dB to OFF			U	U	U	U	U	U
1.5 watt loudspeaker power (peak)	U		U		U		U	
6 watt loudspeaker power (peak)		U		U		U		U
Pre-selectable startup mode for control panel functions							U	U
TALK switch G.P.I. on 9-way "D" plug (COST OPTION)	U	U	U	U	U	U	U	U
24V DC power input on XLR4 socket (COST OPTION)		U		U		U		U